


EC Declaration of Compliance



The undersigned representative

of the Manufacturer: **BOGUMA, s.r.o**
[registered seat and address] **Továrenská 314, 956 18 Bošany**

of the Manufacturing Plant **BOGUMA s.r.o**
[registered address] **Továrenská 314, 956 18 Bošany**

hereby declares that the Product "**Rubber Flooring Material with the S-8 Tread Pattern**"

is in full compliance with the provisions of Council Directive 89/106/EEC, provided it is built-in in compliance with the applicable assembly directions and that the following standard is applied to the manufacture of the Product:

EN 14041: 2004 + EN 14041: 2004/AC: 2005 "Elastic Fabric and Laminate Flooring Materials".
The basic properties/qualities:

The following properties/qualities have been verified through initial type tests:

Property / Quality	Value or Class Declared	Test Report Number and Laboratory Reference
Reaction to fire	E ₁ Class	Z – 22/041/07/3504 (EN 14041, Table 1)
Slipperiness	Dynamic friction coefficient $\mu_a \geq 0.30$	Z – 22/041/07/3504 (NPD) 1)
Permanent deformation	≤ 0.25 mm	Z – 22/041/07/3604 1)
Dimensional stability	± 0.4 %	Z – 22/041/07/3604 1)

Product Description, and the Purpose and Method of Use in a Structure:

The Rubber Flooring Material with the S-8 Tread Pattern (IDEAL) is a type of homogenous flooring material manufactured from synthetic rubber with the thickness of 4 mm, black in colour, having a circular pattern with a diameter of 25 mm with longitudinal protrusions on the front surface, manufactured according to TP 2-06 Technical Specification, 1st Edition. The bottom surface has a fabric impression.

This type of rubber flooring material is available with the width of 1230 mm, and with lengths as per customer request (but no more than 12 metres). The length of 10 metres is recommended. 15 metres up to the width of 3.5 mm and 10 metres up to the width of 4 mm and more). The S-8 rubber flooring material has beveled edges that, upon being put close next to each other, ensure that any interstices between them are fully closed.

Depending on the extent/range of surface's tolerated defects, this flooring material is available in three quality categories: Quality I, Standard Quality, and Quality II. The tolerated defects must not impair the overall appearance.

With respect to the total thickness, pursuant to EN 12199 flooring materials are classified according to EN665 as follows: for thicknesses over 3.5 mm, they are categorized into classes 33-34 (the scope of use - commercial) and 41-43 (the scope of use – light industries).


The product is suitable for the covering of interior floors in both residential and publicly accessible facilities, light industry premises, and means of transportation by sticking them on the underlying surface. Instructions for the process of gluing provided by the manufacturer must be observed and adhered to.

The names and addresses of the laboratories where the tests have been carried out:

- 1) LIGNOTESTING, a.s., SKLMV, Technická 5, SK-82104 Bratislava

Name: *Igor Gulčík*
Position: *Company Executive*
Date: *March 20, 2007*

Signature:


BOGUMA, s.r.o.
Továrenská 314
956 18 Bošany
IČO: 35 922 087
IČ DPH: SK2021963625

